

SAFETY DATA SHEET

according to Regulation (EU) 2015/830

Page 1/6

H889 SILICONE SPRAY

Revision 3
Revision date 2017-10-09

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name	H889 SILICONE SPRAY
Product code	BISR500

1.3. Details of the supplier of the safety data sheet

Company
Address

Web
Telephone
Fax
Email
Email address of the
competent person

1.4. Emergency telephone number

Emergency telephone number	01422 315300 8.30AM - 5.30PM Mon-Fri
----------------------------	---

SECTION 2: Hazards Identification

2.1. Classification of the substance or mixture

2.1.2. Classification - EC 1272/2008	Aerosols 1: H222; Aerosol 1, 2, 3: H229; STOT SE 3: H336; Aquatic Chronic 3: H412;
---	--

2.2. Label elements

Hazard pictograms



Signal Word

Danger

Hazard Statement

Aerosols 1: H222 - Extremely flammable aerosol.
Aerosols, 1, 2, 3: H229 - Pressurised container: May burst if heated.
STOT SE 3: H336 - May cause drowsiness or dizziness.
Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.

Precautionary Statement:
Prevention

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 - Do not spray on an open flame or other ignition source.
P251 - Do not pierce or burn, even after use.
P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.

H889 SILICONE SPRAY

Revision 3
Revision date 2017-10-09

2.2. Label elements

Precautionary Statement: Response	P271 - Use only outdoors or in a well-ventilated area. P273 - Avoid release to the environment.
	P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. P314 - Get medical advice/attention if you feel unwell.
Precautionary Statement: Storage	P403+P233 - Store in a well-ventilated place. Keep container tightly closed. P410 - Protect from sunlight.
	P412 - Do not expose to temperatures exceeding 50°C/ 122°F.
Precautionary Statement: Disposal	P501 - Dispose of contents/container to meet National Legislation and Environmental Regulations

SECTION 3: Composition/Information on Ingredients

3.1. Substances

EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification
Butane	601-004-00-0	106-97-8	203-448-7		30 - 40%	Flam. Gas 1: H220;
Propane	601-003-00-5	74-98-6	200-827-9		30 - 40%	Flam. Gas 1: H220;
aliphatic hydrocarbon.		64742-49-0	265-151-9		10 - 20%	Flam. Liq. 2: H225; Asp. Tox. 1: H304; Skin Irrit. 2: H315; STOT SE 3: H336; Aquatic Chronic 2: H411;

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Move the exposed person to fresh air.
Eye contact	Rinse immediately with plenty of water for 15 minutes holding the eyelids open.
Skin contact	Wash off immediately with plenty of soap and water. Remove contaminated clothing.
Ingestion	DO NOT INDUCE VOMITING.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation	Inhalation may cause coughing, tightness of the chest and irritation of the respiratory system. Irritating to respiratory system.
Eye contact	Irritating to eyes.
Skin contact	Irritating to skin.
Ingestion	Ingestion may cause nausea and vomiting.

4.3. Indication of any immediate medical attention and special treatment needed

Inhalation	Seek medical attention.
Eye contact	Seek medical attention if irritation or symptoms persist.
Skin contact	Seek medical attention if irritation or symptoms persist.
Ingestion	Seek medical attention if irritation or symptoms persist.

SECTION 5: Firefighting measures

5.1. Extinguishing media

	Carbon oxides.
--	----------------

5.2. Special hazards arising from the substance or mixture

	Burning produces irritating, toxic and obnoxious fumes. Vapour may travel considerable distance to source of ignition and flash back.
--	---

5.3. Advice for firefighters

	Self-contained breathing apparatus. Wear protective clothing.
--	---

H889 SILICONE SPRAY

Revision 3
Revision date 2017-10-09**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

	Ensure adequate ventilation of the working area. Wear suitable protective equipment. Eliminate all sources of ignition. Evacuate personnel to a safe area.
--	--

6.2. Environmental precautions

	Do not allow product to enter drains. Prevent further spillage if safe.
--	---

6.3. Methods and material for containment and cleaning up

	Absorb with inert, absorbent material. Sweep up. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.
--	---

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

	Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Use explosion proof equipment. Keep away from sources of ignition - No smoking.
--	--

7.2. Conditions for safe storage, including any incompatibilities

	Keep in a cool, dry, well ventilated area. Keep containers tightly closed. Store in correctly labelled containers.
--	--

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****8.1.1. Exposure Limit Values**

Butane	WEL 8-hr limit ppm: 600	WEL 8-hr limit mg/m3: 1450
	WEL 15 min limit ppm: 750	WEL 15 min limit mg/m3: 1810
	WEL 8-hr limit mg/m3 total -	WEL 15 min limit mg/m3 total -
	inhalable dust:	inhalable dust:
	WEL 8-hr limit mg/m3 total -	WEL 15 min limit mg/m3 total -
	respirable dust:	respirable dust:

8.2. Exposure controls

8.2.1. Appropriate engineering controls	Ensure adequate ventilation of the working area.
8.2.2. Individual protection measures	Wear chemical protective clothing.
Eye / face protection	Approved safety goggles.
Skin protection -	Chemical resistant gloves (PVC).
Handprotection	
Respiratory protection	Wear suitable respiratory equipment when necessary.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

H889 SILICONE SPRAY

Revision 3
Revision date 2017-10-09

9.1. Information on basic physical and chemical properties

Appearance	Aerosol
Colour	Clear
Odour	Characteristic
pH	No data available
Melting point	No data available
Freezing Point	No data available
Initial boiling point	No data available
Evaporation rate	No data available
Flammability (solid, gas)	No data available
Upper Explosive Limit	9.5 %
Lower Explosive Limit	1.8 %
Vapour pressure	No data available
Vapour density	No data available
Fat Solubility	No data available
Partition coefficient	No data available
Viscosity	No data available
Explosive properties	No data available
Oxidising properties	No data available
Solubility	Insoluble in water

9.2. Other Information

Conductivity	No data available
Surface tension	No data available
Gas group	No data available

SECTION 10: Stability and reactivity

10.2. Chemical stability

	Stable under normal conditions.
--	---------------------------------

10.3. Possibility of hazardous reactions

	Oxidising agents.
--	-------------------

10.4. Conditions to avoid

	Heat, sparks and open flames.
--	-------------------------------

SECTION 11: Toxicological Information

11.1.4. Toxicological Information

	No data available
--	-------------------

SECTION 12: Ecological Information

12.1. Toxicity

	No data available
--	-------------------

12.3. Bioaccumulative potential

Partition coefficient

	H889 SILICONE SPRAY No data available
--	---------------------------------------

SECTION 13: Disposal considerations

13.1. Waste treatment methods

	Dispose of as special waste in compliance with local and national regulations.
--	--

H889 SILICONE SPRAY

Revision 3
Revision date 2017-10-09

SECTION 14: Transport Information

Hazard pictograms



14.1. UN number

UN1950

14.2. UN proper shipping name

AEROSOLS

14.3. Transport hazard class(es)

ADR/RID	2
Subsidiary risk	see SP63
IMDG	2
Subsidiary risk	see SP63
IATA	2
Subsidiary risk	see SP63

14.4. Packing group

Packing group

-

14.5. Environmental hazards

Environmental hazards	No
Marine pollutant	No

ADR/RID

Hazard ID	-
Tunnel Category	(D)

IMDG

EmS Code	F-D S-U
----------	---------

IATA

Packing Instruction (Cargo)	203
Maximum quantity	150 kg
Packing Instruction (Passenger)	203
Maximum quantity	75 kg

Further Information

The product is not classified as dangerous for carriage.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulations	REGULATION (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC. COMMISSION REGULATION (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No
-------------	--

H889 SILICONE SPRAY

Revision 3
Revision date 2017-10-09

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

15.2. Chemical safety assessment

No data is available on this product.

SECTION 16: Other Information

Other information

Revision	This document differs from the previous version in the following areas: 2 - 2.1.2. Classification - EC 1272/2008. 2 - Precautionary Statement: Prevention. 2 - Precautionary Statement: Response. 2 - Precautionary Statement: Storage. 9 - 9.1. Information on basic physical and chemical properties (Flash point). 9 - 9.1. Information on basic physical and chemical properties (Autoignition temperature). 9 - 9.1. Information on basic physical and chemical properties (Relative density). 9 - 9.1. Information on basic physical and chemical properties (Upper Explosive Limit). 9 - 9.1. Information on basic physical and chemical properties (Lower Explosive Limit).
Text of Hazard Statements In Section 3	Flam, Gas 1: H220 - Extremely flammable gas. Flam, Liq. 2: H225 - Highly flammable liquid and vapour. Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways. Skin Irrit. 2: H315 - Causes skin irritation. STOT SE 3: H336 - May cause drowsiness or dizziness. Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.

Further Information

	The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.
--	---